





2. 00mm Female Header, Single/Dual Row

SPECIFICATIONS





Current Rating: 2.0AMP
 Contact Resistance: 20m Ω Max.
 Insulation Resistance: 1000M Ω Min.
 Withstanding Voltage :500V AC/Minute
 Operation Temperature: -55°C to+125°C
 Contact Material: Phosphor Bronze
 Contact plating: Au or Sn Over Ni
 Insulator Material: Polyester (UL94V-0)
 Standard: PA6T+30%GF



2246-X XX X XX X UN X X

| | | | | | |
|---|-------------------------------------|--|---|--|--|
| NO.OF ROW 1:Single Row 2: Dual Row | NO.OF PINS PER ROW 02~40P | CONTACT SHAPE S: Straight M: 180° SMT C: K Feet/Splint | CONTACT PLATING G0: 1u" Gold G1: 3u" Gold G2: 5u" Gold G3: 10u" Gold G4: 15u" Gold G5: 30u" Gold G6: 20u" Gold | INSULATOR MATERIAL C: PA6T D: LCP | PACKING T: Tube R: Tape & Reel P: Tube+CAP |
| | | | S0: 1u" Gold/Tin S1: 3u" Gold/Tin S2: 5u" Gold/Tin S3: 10u" Gold/Tin S4: 15u" Gold/Tin S5: 30u" Gold/Tin S6: 20u" Gold/Tin SN: Tin | | |



※ INNOVATION AND DEVELOPMENT ※ CONTINUAL IMPROVEMENT ※ QUALITY FOREMOST ※ CUSTOMER SATISFACTION ※

Http:www.wafe-china.com E-mail:sales@wafe-china.com

WAFE DONGGUAN FAX:+86 769 85358915 TEL:+86 769 85358920
 WAFE KUNSHAN FAX:+86 512 57468468 TEL:+86 512 57468418