



2185-2XXSXXXYNX2

2. 54mm Female Header, Single/Dual Row


SPECIFICATIONS




Current Rating: 3.0AMP
 Contact Resistance: 20mΩ Max.
 Insulation Resistance: 1000MΩ Min.
 Withstanding Voltage :1000V AC/Minute
 Operation Temperature: -40°C to+105°C
 Contact Material: Brass/Phosphor Brass
 Contact plating: Au or Sn Over Ni
 Insulator Material: Polyester (UL94V-0)
 Standard: PBT+30%GF




2185-1XXSXXXYNX1



2185-1XXRXXXYNX1



2185-2XXSXXXYNX1



2185-2XXRXXXYNX1

2185-X XX X XX X YN X X

NO.OF ROW
 1:Single Row
 2:Dual Row

NO.OF PINS PER ROW
 02~40P



CONTACT SHAPE
 S: Straight
 R: Right Angle

CONTACT PLATING
 G0:1u" Gold S0:1u" Gold/Tin
 G1:3u" Gold S1:3u" Gold/Tin
 G2:5u" Gold S2:5u" Gold/Tin
 G3:10u"Gold S3:10u"Gold/Tin
 G4:15u"Gold S4:15u"Gold/Tin
 G5:30u"Gold S5:30u"Gold/Tin
 G6:20u"Gold S6:20u"Gold/Tin
 SN:Tin

INSULATOR MATERIAL
 A:PBT
 C:PA6T
 D:LCP



PACKING
 A:Tray T:Tube

SINGLE ROW



Recommended P. C. B Layout (Top Side)

DUAL ROW



Recommended P. C. B Layout (Top Side)

※ INNOVATION AND DEVELOPMENT ※ CONTINUAL IMPROVEMENT ※ QUALITY FOREMOST ※ CUSTOMER SATISFACTION ※

Http:www.wafe-china.com E-mail:sales@wafe-china.com

WAFE DONGGUAN FAX:+86 769 85358915 TEL:+86 769 85358920
 WAFE KUNSHAN FAX:+86 512 57468468 TEL:+86 512 57468418