

2195-1XXMXXXUNX1





2195-1XXMXXXUNX2

2. 54mm Female Header, Single/Dual Row


SPECIFICATIONS




Current Rating: 3.0AMP
 Contact Resistance: 20mΩ Max.
 Insulation Resistance: 1000MΩ Min.
 Withstanding Voltage :1000V AC/Minute
 Operation Temperature: -40°C to +105°C
 Contact Material: Phosphor Bronze
 Contact plating: Au or Sn Over Ni
 Insulator Material: Polyester (UL94V-0)
 Standard: PA6T+30%GF



2195-1XXSXXXUNX1



2195-2XXSXXXUNX1



2195-2XXMXXXUNX1

2195-X XX X XX X UN X X

NO.OF ROW
 1:Single Row
 2: Dual Row


NO.OF PINS
 PER ROW
 02~40P

CONTACT SHAPE
 S: Straight
 M: 180°SMT

CONTACT PLATING
 G0:1u" Gold S0:1u" Gold/Tin
 G1:3u" Gold S1:3u" Gold/Tin
 G2:5u" Gold S2:5u" Gold/Tin
 G3:10u"Gold S3:10u"Gold/Tin
 G4:15u"Gold S4:15u"Gold/Tin
 G5:30u"Gold S5:30u"Gold/Tin
 G6:20u"Gold S6:20u"Gold/Tin
 SN:Tin

INSULATOR MATERIAL
 C:PA6T
 D:LCP

PACKING
 T:Tube
 R:Tape & Reel



※ INNOVATION AND DEVELOPMENT ※ CONTINUAL IMPROVEMENT ※ QUALITY FOREMOST ※ CUSTOMER SATISFACTION ※

Http:www.wafe-china.com E-mail:sales@wafe-china.com

WAFE DONGGUAN FAX:+86 769 85358915 TEL:+86 769 85358920
 WAFE KUNSHAN FAX:+86 512 57468468 TEL:+86 512 57468418