WCON®
HTTP:WWW.WAFE-CHINA.COM

2.54mm DIN 41612 IDC Type Female Connector

SPECIFICATIONS

FILE NO.E248993

Current Rating: 3.0AMP
Contact Resistance: 30mΩ Max.
Insulation Resistance: 1000MΩ Min.
Withstanding Voltage : 1000V AC/Minute
Operation Temperature: −55°C to+105°C
Contact Material: Brass
Contact plating: Au or Sn Over Ni
Insulator Material: Polyester (UL94V−0)
Standard: PBT+30%GF





3410-3 XX X F I XX N A 1

NO.OF PINS
2X16P and
2X32P

TERMINAL ALLOT
B=a+b
D=a

CONTACT	PLATING
G0:1u" Gold	S0:1u" Gold/Tin
G1:3u" Gold	S1:3u" Gold/Tin
G2:5u" Gold	S2:5u" Gold/Tin
G3:10u"Gold	S3:10u"Gold/Tin
G4:15u"Gold	S4:15u"Gold/Tin
G5:30u"Gold	S5:30u"Gold/Tin
G6:20u"Gold	S6:20u"Gold/Tin
SN:Tin	



※ ※INNOVATION AND DEVELOPMENT ※ ※CONTINUAL IMPROVEMENT ※ ※QUALITY FOREMOST ※ ※CUSTOMER SATISFACTION ※ ※

Http:www.wafe-china.com E-mail:sales@wafe-china.com
WAFE DONGGUAN FAX:+86 769 85358915 TEL:+86 769 85358920
WAFE KUNSHAN FAX:+86 512 57468468 TEL:+86 512 57468418