

HSPF

TECHNICAL SPECS:

Current Rating: 3.0AMP
 Contact Resistance: 10mΩ Max
 Dielectric Strength: Min 1000Vrms
 Mechanical Life: Min 500 cycles
 Mating Pin: $\phi 0.40$ to $\phi 0.66$ mm or 0.505SQ
 Forces: (polished steel gauge $\phi 0.46$ mm)
 -Insertion: 0.7N typ. -Withdrawal: 0.4N typ.
 Operation Temperature: -40°C to +105°C

Sleeve: Brass CuZn36Pb3(C36000)

Contact Clip(4 finger): BeCu(C17200)

Contact plating: Au or Sn over Ni

Insulator Material: PPS+30%G.F.(UL94V-0)

Ordering Information




3522-282 XX S XX 147 X 1

No. of Pin
2-40PIN

Contact Plating
 G0=Gold Flash
 G1=3u"Gold
 G2=5u"Gold
 G3=10u"Gold
 G4=15u"Gold
 G5=30u"Gold

Packing
 A=Tray
 T=Tube

S0=Gold Flash/Tin
 S1=3u"Gold/Tin
 S2=5u"Gold/Tin
 S3=10u"Gold/Tin
 S4=15u"Gold/Tin
 S5=30u"Gold/Tin
 SN=Tin



REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE	OPERATION	DRAW	WEIXD	SCALE	PART NO.	TITLE:
A0	08/10/13	NEW			X.X ±0.40	DESIGN	08/10/13	1:1	3522-282XXSX147X1	2.00mm MACHINED FEMALE HEADER DIAL ROW 180° H=2.80 L=14.7
					X.XX ±0.25	CHECK		A4		
					X.XXX ±0.15	CHECK		1/1		
					Angle ± 3'	APPROVE			Customer NO.	

WCON 维峰五金电子有限公司
 WAVE HARDWARE ELECTRONICS CO.,LTD