


D-sub Connector IDC Type


SPECIFICATIONS



Current Rating: 3.0AMP
 Contact Resistance: 20m Ω Max.
 Insulation Resistance: 1000M Ω Min.
 Withstanding Voltage : 500V AC/Minute
 Operation Temperature: -55°C to +105°C
 Contact Material: Phosphor Bronze/Brass
 Contact plating: Au or Tin Over Ni
 Insulator Material: Polyester (UL94V-0)
 Standard: PBT+30%GF
 Shell: Cold Roller Steel ,Ni Plated
 Nut: Brass ,Tin Over Ni Plated



6224-XXMXXU01



6224-XXFXXU01



6224- XX X XX U 01

NO.OF PINS
9,15,25,37P

TYPE
M:Male
F:Female

CONTACT PLATING
 G0:1u" Gold S0:1u" Gold/Tin
 G1:3u" Gold S1:3u" Gold/Tin
 G2:5u" Gold S2:5u" Gold/Tin
 G3:10u" Gold S3:10u" Gold/Tin
 G4:15u" Gold S4:15u" Gold/Tin
 G5:30u" Gold S5:30u" Gold/Tin
 G6:20u" Gold S6:20u" Gold/Tin
 SN: Tin

INSULATOR COLOR
 B:Black W:White
 U:Blue G:Grey



※ INNOVATION AND DEVELOPMENT ※ CONTINUAL IMPROVEMENT ※ QUALITY FOREMOST ※ CUSTOMER SATISFACTION ※

Http:www.wafe-china.com E-mail:sales@wafe-china.com

WAFE DONGGUAN FAX:+86 769 85358915 TEL:+86 769 85358920
 WAFE KUNSHAN FAX:+86 512 57468468 TEL:+86 512 57468418